

Omnican OC-45

- Exclusive OMNIGUIDE technology for immersive 360-degree sound dispersion
- Perfect for in-ceiling complete home theater application
- Indoor or outdoor installation; weather resistant construction
- Rotatable OMNIGUIDE allows fine-tuning of sound in the listening area
- Low profile design
- Woofers feature Ribbed Elliptical Surround™ for increased output and lower distortion
- Easy installation, setup
- Removable back boxes for ease of installation in tight spaces
- Paintable grille and bezel



Specifications	
DESIGN:	Weather resistant Omnipolar in-ceiling speaker
SYSTEM TYPE:	2-Way
RECOMMENDED AMPLIFIER POWER:	10 to 100 Watts
NOMINAL IMPEDANCE:	8 Ohms
MINIMUM IMPEDANCE:	4 Ohms
FREQUENCY RESPONSE (+/- 3DB):	110 Hz - 20 kHz
SENSITIVITY (1W/1M):	88 dB
CROSSOVER POINT:	2.7 kHz
TWEETER:	1" PTH™ Pure Titanium Hybrid tweeter
WOOFER:	4.5" Titanium Deposit Polypropylene woofer with patented Ribbed Elliptical Surround
HEIGHT:	6.3" / 16 cm (1.6" / 4 cm visible height when installed)
WIDTH:	W - 6.89" / 17.5 cm (back box) W - 8.4" / 21.36 cm (outside baffle)
RECOMMENDED HOLE CUT-OUT:	Ø 7.0625 / 18 cm
REQUIRED INSTALLATION DEPTH:	4.46" / 11.3 cm
CONNECTORS:	High quality spring loaded
PACKAGING QUANTITY:	1 per box
COLORS:	White
OTHER UNIQUE FEATURES:	Weather resistant design with UV rated enclosure. Rotatable OMNIGUIDE module
OPTIONAL INSTALLATION BRACKET:	ICB-45